

# AHD 5 in 1 1080P DVR 16CH

Picture



Support 16ch 1080P non real-time encoding;  
 Support AHD, TVI, CVI, CVBS, IP video input;  
 HDMI/VGA simultaneous video output;  
 2U Case, 2 SATA (Up to 4TB);  
 1\*10/100Mbps auto-sensing Ethernet port, RJ45 port;  
 Automatic networking support, a key to add equipment;  
 Cloud services, P2P, alarm information push to phone;  
 Support remote access, support ARSP;  
 Mobile phone remote monitoring (iOS, Android);  
 Multi browser access (IE, Chrome, Firefox, Safari);  
 Perfect protection circuit, unique triple watchdog function;  
 Support WEB, CMS, VMS, Cloudsee Platform;

## SPECIFICATION

	Model	GN-5216N(V-XT2616-S2)	
System	Processor	Hi3521A	
Video	Codec	H.264	
	Encode	16*1080P@18fps	
	Decode	16*1080P@18fps	
	Multi-mode		Analog:16*1080N@18fps
			Hybird: 8*1080P(analog)+8*1080P(ip)
		IP:16*1080P	
	Playback	16ch	
Audio	Compression	G.711a	
	Intercom	Support	
Management	Record mode	Manual>Alarm>Motion detection>Timing	
	Inquire mode	Inquire by Time/Calendar/Event/Channel	
	Storage Mode	HDD Storage, Network Storage	
	Backup	Network, USB, SATA	
Inerface	Video input	16*BNC(Support Coaxitron)	
	HDMI output	1*HDMI	
	VGA output	1*VGA	
	Audio I/O	2	
	Alarm I/O	Optional	
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port	
	PTZ contorl	1*RS485, Support for multiple PTZ protocol	
	USB port	2*USB2.0 ports	
	HDD	2*SATA interface (Up to 4TB)	
General	Temperature	0℃- + 55℃	
	Humidity	10% -90% RH	
	Power supply	12V/4A	
	Consumption	<10W(Without HDD)	