

Main Features



- 1/2.8" 2MP SONY EXmor CMOS
- AHD Video(1080P)
- High rate, long-distance, real-time transmission
- D-WDR, 2D/3D DNR ,Defog, Digital Slow Shutter
- Auto Defog, HLC, Privacy mask, motion detection
- AHD/CVBS Signal Selectable from OSD
- Multi Languages OSD control
- Power supply: DC12V

Specifications

Model No.	RT-4222
Image Sensor	1/2.8" 2MP SONY EXmor CMOS
Resolutions	Digital: 2.43M pixels, Analog: 960H
Max Video Resolution	1984(H)*1225(V)
Min. Illumination	0.01Lux (0Lux IR on)
Video Output	AHD/CVBS (Signal Selectable from OSD)
S/N Ratio	≥80dB(AGC OFF)
Day & Night	EXT,COLOR, B&W,AUTO
White Balance	AWB,AWC→SET,Indoor,Outdoor,Manual
DNR	2D/3D NR
WDR	OFF/ON/Auto
Defog	OFF/ON
Backlight	OFF/BLC/HSBLC
Privacy Mask	ON/OFF(4 Zones)
Motion Detect	ON/OFF(4 Zones)
Baudrate	2400/4800/9600/19200/38400
IR LED	3pcs Array LED
IR Range	40m
Lens	3.6mm
Input Voltage	DC12V±10%
Current	320mA
Power Consumption	<4W
Weight	450g
IP Rating	IP66
Operation Temp.	-10℃~+50℃
Storage Humidity	<90%RH (no condensation)

Dimensions

